

# CONFORMITY CERTIFICATE

## N° 17.6.0238/A

### 1. Applicant

Applicant: M. David Callejas  
Manufacturer: FALLPROTEC – 43-45, ZA Op Zaemer – 4959 BASCHARAGE - Luxembourg

### 2. Equipment

Type of anchor: Anchor device type D – standard EN 795:2012 and Technical Specification TS 16415:2013  
Trademark: **FALLPROTEC**  
Model: **NAV2**

### 3. DESCRIPTION

Anchor device type D, made up of:

- Rigid anchor line by rail, in aluminium EN AW6060 T6, 63.2x112.5x15.5mm, SAFEACCESS, MHS059. Span maxi. 6m. Rail length 3 and 6m. Fixing by mounting bracket, MHS061.
- No opening carriage in stainless steel, four guiding wheels, integrating a metallic ring anchor, MHS023 NAV 2
- End stop on side to the rail, MHS017
- Link junction in aluminium alloy 6060 T66, 295 mm, MHS075. Allowed wherever all along the span.
- Cantilever at 500mm.

Use ceiling, by 4 people (detailed in the conformity report 17.6.0238).

### 4. Technical referential

The anchor device Type D, assessed taking into account the provisions of technical specification TS 16415:2013 on anchor device type conforms to EN 795:2012 to the exclusion of any other standard.

### 5. CONDITION USE

This anchor device type D, is not considered as personal protective equipment against falls from a height.  
This anchor device type D is intended to be used, in combination with other components, as personal protective equipment against falls from a height.

### 6. CONCLUSION

The Anchor device Type D of reference **NAV2**, presented by FALLPROTEC, conforms to the requirements of European standard EN 795:2012 and of the Technical Specification TS 16415:2013.

01/08/2017

PPE Technical Manager

Document original immatériel

